Application No. 10/623,576   Docket No.: 3722-0155P
Amendment dated November 7, 2006
After Final Office Action of September 8, 2006

AMENDMENTS TO THE CLAIMS

1.   (Currently Amended) An ADIP demodulation apparatus, which is applied to an optical disk driver to generate ADIP information according to a wobble signal, the ADIP demodulation apparatus comprising:

a slicing unit for receiving the wobble signal and generating a wobble pulse by slicing the wobble signal;

a phase locked loop for generating a reference wobble signal with the same frequency and phase as the wobble pulse according to the wobble pulse;

a channel bit generator for producing a channel bit signal according to a difference signal generated by comparing the phase of the reference wobble signal with that of the wobble pulse generating a channel bit signal according to the reference wobble signal and the wobble pulse; and

a decoder for decoding to the ADIP information according to the channel bit signal;

wherein the channel bit generator comprises:

a bit comparator for receiving the wobble pulse and the reference wobble signal and generating the difference signal;

a counter for counting the width of high level of the difference signal corresponding to each wobble pulse using a counting clock and outputting a count value; and

a decision unit for comparing the count value with a threshold value and then outputting the channel bit signal.

wherein the channel bit generator produces the channel bit signal according to a difference signal generated by comparing the phase of the reference wobble signal with that of

2   KM/asc

Application No. 10/623,576   Docket No.: 3722-0155P
Amendment dated November 7, 2006
After Final Office Action of September 8, 2006

~~the wobble pulse.~~

2.   (Cancelled)

3.   (Currently Amended) The ADIP demodulation apparatus according to claim [[2]] 1,

further comprising a reference clock generator for generating the counting clock according to the

wobble pulse.

4.   (Currently Amended) The ADIP demodulation apparatus according to claim [[2]] 1,

wherein the ADIP information is a sync signal when the channel bit signal sequence is a first

sequence.

5.   (Previously Presented) The ADIP demodulation apparatus according to claim 4,

wherein the ADIP information is data 0 when the channel bit signal sequence is a second

sequence.

6.   (Previously Presented) The ADIP demodulation apparatus according to claim 5,

wherein the ADIP information is data 1 when the channel bit signal sequence is a third sequence.

7.   (Cancelled)

8.   (Cancelled)

9.   (Cancelled)

10. (Cancelled)

11. (Cancelled)

12. (Cancelled)

13. (Previously Presented) The ADIP demodulation apparatus according to claim 1,

wherein the difference signal is generated by executing an XOR operation between the reference

wobble signal and the wobble pulse.

3   KM/asc

14. (Previously Presented) The ADIP demodulation apparatus according to claim 1, wherein the difference signal is generated by executing minus operation between the reference wobble signal and the wobble pulse.

15. (Previously Presented) The ADIP demodulation apparatus according to claim 4, wherein the first sequence is 11110000.

16. (Previously Presented) The ADIP demodulation apparatus according to claim 5, wherein the first sequence is 10000011.

17. (Previously Presented) The ADIP demodulation apparatus according to claim 6, wherein the first sequence is 10001100.

18. (Cancelled)

19. (Cancelled)

20. (Cancelled)

4

KM/asc